

**Company**

**Phone**

**Contact**

**Telefax**

**E-Mail**

2/2 way       Solenoid valve system       Pressure controlled valve system

3/2 way       Spare parts for valve type

5/2 way       Service set number

**Function Solenoid valve systems**

**NC** - non energized closed       **NO** - non energized open       **UN** - universal (each inlet can be used as "p")

**Function Pressure controlled valve**

**NC** - normally closed by spring power, in flow direction       **NC** - normally closed by spring power, against flow direction (Anti-Waterhammer)

**NO** - normally open by spring power       **DW** - double acting actuator

**Quantity**  unit(s)

**Materials** Body:  Seal:

**Connection** Threaded G:  Flanged DN:  PN:

**Pressure range** p1:  P2:  Op:  bar

**Temperature range** Medium temp.  °C Ambient temp.  °C

**Flow medium**  Viscosity  mm<sup>2</sup>/sec (centistokes)

**Flow factor**  m<sup>3</sup>/h requested flow rate:  l/min  m<sup>3</sup>/h

**Mounting**

Actuator in any position       Actuator only in upright position       Actuator preferable in upright position

**Supply voltage** V:  Hz (AC):  Watt (DC):

**Ex proof**  Yes  No class:

**Further remarks/optional extras**

**Delivery time, required**  days/weeks